

HAZARD STATEMENT:

May be harmful if swallowed.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Causes damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

Prevention: Do not breathe dust/fume/gas/mist/vapors/spray.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.

Response: Get Medical advice/attention if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

Safety Data Sheet
Number SDS-00016



Danger

Ocal™

PATCHING COMPOUND FOR PVC

PATCHG-B
Blue GID# 7TAA087990R0388

ONE
Gallon / 3.79 Liters

- **For Use with Ocal™ Coated Conduit and Accessories**
CAREFULLY READ ALL CAUTIONS AND DIRECTIONS BEFORE USE

 **WARNING**

This product can expose you to Titanium dioxide, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.


by ABB

DIRECTIONS:

1. Shake well before using.
2. Thoroughly clean and dry area to be patched.
3. Apply Ocal™ Patching Compound to damaged area with brush. Multiple layers may be used if a larger build is required.
4. Allow to dry 1 to 4 hours. For optimum results, allow to age overnight.

Limited Warranty Applies.

Refer to: tnb.abb.com/ecpwarranty for full warranty terms.

Supplier Identification:

ABB Installation Products Inc.
860 Ridge Lake Boulevard, Memphis,
Tennessee 38120 - electrification.us.abb.com
U.S.A.

EMERGENCY NUMBER: 1-800-535-5053

Country of Origin: United States

©2024 ABB Installation Products Inc. and/or its related companies.
All Rights Reserved.

