HAZARD STATEMENT:

May be harmful if swallowed.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.



PRECAUTIONARY STATEMENTS:

Do not breathe dust/fume/gas/mist/vapors/spray Avoid breathing dust/fume/gas/mist/vapors/spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area. Response: Get Medical advice/attention if you feel unwell IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Prevention: Obtain special instructions before use.

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

Safety Data Sheet Number SDS-00019



PATCHING COMPOUND FOR PVC

PATCHP-W White GID# 7TAA087990R0395

Net Contents: 16 Fl oz. / .47 Liters

 For Use with Ocal™ Coated Conduit and Accessories CAREFULLY READ ALL CAUTIONS AND DIRECTIONS BEFORE USE



This product can expose you to Titanium dioxide, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.



DIRECTIONS:

- 1. Shake well before using.
- 2. Thoroughly clean and dry area to be patched.
- 3. Apply Ocal™ Patching Compound to damaged area with brush. Multiple layers may be used if a larger build is required.
- 4. Allow to dry 1 to 4 hours. For optimum results, allow to age overnight.

Limited Warranty Applies.

Refer to: tnb.abb.com/ecpwarranty for full warranty terms.



ABB Installation Products Inc. 860 Ridge Lake Boulevard, Memphis, Tennessee 38120 - electrification.us.abb.com

EMERGENCY NUMBER: 1-800-535-5053

companies. All Rights Reserved.

Country of Origin: United States
©2025 ABB Installation Products Inc. and/or its related



TA04176 H