

HAZARD STATEMENT:

Pressurized container: may burst if heated.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May damage fertility or the unborn child.

Causes damage to organs.

Causes damage to organs through prolonged or repeated exposure.



Danger

PRECAUTIONARY STATEMENT:

Prevention: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces - No smoking. Do not spray on an open flame or other ignition source. Pressurized container - Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.

Response: IF exposed or concerned: Get medical advice/attention. Specific treatment (see Section 4 in SDS). IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF ON SKIN: Wash with soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If eye irritation persists, get medical advice/attention. IF exposed: Call a POISON CENTER or doctor/physician.

Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

Ocal™

PVC PATCHING COMPOUND

SPRAY-W
White

ONE

Net Contents:

GID# 7TAA087990R0424

12.5 Fl oz. / .37 Liters

**For Use with Ocal™ Coated
Conduit and Accessories**

**CAREFULLY READ ALL CAUTIONS
AND DIRECTIONS BEFORE USE**

WARNING

This product can expose you to chemicals including Toluene and Methyl isobutyl ketone, which are known to the State of California to cause cancer, birth defects or reproductive harm. For more information go to www.P65Warnings.ca.gov.

Safety Data Sheet
Number SDS-00026

by ABB

DIRECTIONS:

1. Shake well before using.
2. Thoroughly clean and dry area to be patched.
3. Spray Ocal™ PVC Patching Compound on damaged area, holding the spray can 6 to 8 inches from the surface. Multiple layers may be used if a larger build is required.
4. Allow to dry 1 to 4 hours. For optimum results, allow to age overnight.

Limited Warranty Applies.

Refer to: tnb.abb.com/ecpwarranty for full warranty terms.



Supplier Identification:

ABB Installation Products Inc.
860 Ridge Lake Boulevard, Memphis,
Tennessee 38120 - electrification.us.abb.com
U.S.A.

EMERGENCY NUMBER: 1-800-535-5053

Country of Origin: United States

©2024 ABB Installation Products Inc. and/or
its related companies. All Rights Reserved.

TA04182 F