



HM 52 (1/2 PINT)

OXIDE INHIBITING COMPOUND

GID# 7TAA265950R0002

For Full Tension Splices Only.
Mfg. Part # 195-23390

ONE
Net Contents:
8 FL. OZ.

Directions:

- 1) To open sealed spout, cut off approximately $\frac{3}{8}$ " from end.
- 2) Thoroughly clean all conductors and conductor contact surfaces with a stainless steel wire brush.
- 3) Apply a generous coating of compound to all prepared surfaces.
- 4) Remove all excess compound from parts after installation.



 **by ABB**

PRECAUTIONARY STATEMENT:

Prevention: Observe good industrial hygiene practices.

Response: Wash hands after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of waste and residues in accordance with local authority requirements.

For product information call 800-816-7809

For emergencies only. Call INFOTRAC:

+1 800-535-5053

**Safety Data Sheet
Number SDS-00040**

Limited Warranty Applies.


Refer to: tnb.abb.com/ecpwarranty for full warranty terms.

Supplier Identification:

ABB Installation Products Inc.
860 Ridge Lake Boulevard
Memphis, Tennessee, 38120
electrification.us.abb.com

Country of Origin: United States

© 2024 ABB Installation Products
Inc. and/or its related companies.
All Rights Reserved.



TA04979 B