

Cat. No. 15-231

GID # A008400R0003

WIRE PULLING LUBRICANT

For use on Rubber, Neoprene, Nylon, Polyvinylchloride, High Density Polyethylene, Cross-linked Polyethylene, and Lead Covered Wire and Cable – including types R, RH, RHH, RHW, T, TW, THW, THHN, THWN, HDPE, XLPE and XHHW. For use in Steel, Aluminum and other approved conduits. Contains no silicones.



CAUTION



Not for use on Asbestos or Low Density Polyethylene Insulated Cables.

WARNING

Lubricant is conductive while still wet. Allow adequate drying time before energizing circuits. Use great care to be certain that wet material does not come in contact with live or energized electrical parts or equipment.

**FAILURE TO OBSERVE THIS WARNING MAY
CREATE AN ELECTRICAL SHOCK HAZARD.**

ONE
Net Contents:
1 Gallon (3.1 Liters)

by **ABB**

HAZARD STATEMENT:

May cause an allergic skin reaction. Causes serious eye irritation.

PRECAUTIONARY STATEMENT:

Prevention: Wear eye or face protection.

Response: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

For product information call 800-816-7809

For emergencies only. Call INFOTRAC: +1-800-535-5053



Warning

Safety Data Sheet Number SDS-00038

Limited Warranty Applies.

Refer to: tnb.abb.com/ecp/warranty for full warranty terms.

Supplier Identification:

ABB Installation Products Inc.
860 Ridge Lake Boulevard
Memphis, Tennessee, 38120
U.S.A.
electrification.us.abb.com

Country of Origin: United States

©2025 ABB Installation Products Inc. and/or its related companies. All Rights Reserved.

TA05027 B