

CONDUIT TAPPING & THREADING OIL

Cat. No. **15-112**

Contains No Ozone Depleting Substances

USE FOR:

- Threading Rigid Steel
- Aluminum Conduit
- Cutting Tools
- Threading Tools
- Dies

ADVANTAGES:

- Speeds work.
- Prolongs tool life and cutting edge.
- Lubricates and cools the cutting point.
- Eliminates scoring and chatter marks.
- Prevents rust on newly machined parts.



CAUTION



Contains Combustible liquid.
(Read additional warnings and directions on this container.)

For product information call 800-816-7809
For emergencies only. Call INFOTRAC:
+1-800-535-505

GID# 7TAA008400R0001

by ABB

ONE
Net Contents:
1 Gallon / 7.6 lbs.

NOW! One Cutting Oil Does It All From Pipe and Conduit Threading to Machine Shop Applications...

Conduit Tapping & Threading Oil

This oil is a premium petroleum type cutting oil, chemically compounded to provide an excellent lubricant and coolant for heavy duty threading, cutting, tapping and drilling. It can be used on all types of metals both ferrous and non-ferrous for a wide range of metal cutting and threading operations.

NOTE: This container is made of break resistant material, however, some care should be taken when handling.

Applications:

- Threading
- Drilling
- Sawing
- Grinding
- Power Threaders
- Automatic Screw Machines
- Gear Cutters
- Grinders
- Tapping
- Cutting
- Milling
- General Machining
- Hand Threaders
- Turret Lathes
- Brochers

PRECAUTIONARY STATEMENT:

Prevention:

Observe good industrial hygiene practices.

Response:

Wash hands after handling.

Storage:

Store away from incompatible materials.

Disposal:

Dispose of waste and residues in accordance with local authority requirements.

Safety Data Sheet Number SDS-00039



CAUTION



IN CASE OF A FIRE. Use dry chemical, Halon and carbon dioxide. Foam and water fog are effective but may cause frothing.

May Cause Skin or Eye Irritation. Avoid skin and eye contact. Wash thoroughly after handling.

Misuse of Container Can Be Hazardous. Empty containers can be dangerous if used to store toxic, flammable, or reactive materials. Do not pressurize or expose to open flame or head. Keep containers closed. Do not reuse before commercial cleaning.

Limited Warranty Applies. Refer to: tnb.abb.com/ecpwarranty for full warranty terms.

Supplier Identification:

ABB Installation Products Inc.
860 Ridge Lake Boulevard
Memphis, Tennessee, 38120
U.S.A.
electrification.us.abb.com

Country of Origin: United States

©2025 ABB Installation Products Inc. and/or its related companies. All Rights Reserved.

TA05032 B

