

TECHNICAL DATA SHEET - INTERACTIVE PDF

Elbow, rigid

Female to female pulling elbow





Rigid pulling elbows for use with rigid and IMC conduit systems.

Certifications / Standards:





3-Part Specification: 26 05 33.52 End User Tools

Features & Benefits:

- Flush design leaves no broken or bent stubs for easy removal of undamaged forms
- Design leaves a neat, uncluttered job
- Precision cast and machined surfaces permit safer wire pulling

Applications:

- Provides flush threaded conduit hub for mounting, pulling and future access to the conduit system
- Designs permit prefabrication of in-slab conduit system
- Makes 90° bends in conduit runs

Product selection - inches				
Part no.	Hub Size	Α	В	С
APEF-1	1/2"	0.85	0.92	0.92

0.79

Note: Product must be installed in accordance with applicable national and local electrical codes.


Conforms to:

- UL 514B
 - UL File: E23018
- CSA C22.2 No.18
- CSA File 16807

Material

1.17

- Body: Die cast zinc alloy
- Cover: Stamped aluminum alloy
- Gasket: Neoprene
- Screws: Zinc-plated steel



tnb.abb.com (US/Latin America) tnb.ca.abb.com (Canada) abb.com

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction – in whole or in part – is forbidden without prior written consent of ABB. © 2021 ABB Installation Products Inc. and/or its related companies. All Rights Reserved.