

TECHNICAL DATA SHEET - INTERACTIVE PDF

Connectors, compression Cast iron / Zinc plated

Steel City[®]

1



Features:

- Cast iron bodies
- Zinc-plated steel locknuts
- Concrete-tight

Applications:

• Used to join conduit to an enclosure

Compression connectors:

	election and d			
Part no.	Conduit	Α	В	с
	(trade size)	(flat-to-flat)	(O.D.)	
HC401	1/2"	1.23	¹⁄₂"- 14 NPS	0.41
HC402	3/4"	1.36	3⁄4"- 14 NPS	0.45
HC403	1"	1.69	1" - 11.5 NPS	0.44
HC404	11⁄4"	2.15	1¼" - 11.5 NPS	0.56
HC405	1½"	2.40	1½" - 11.5 NPS	0.59
HC406	2"	2.88	2" - 11.5 NPS	0.81
HC407	2 ¹ /2"	3.83	21⁄2" - 8 NPT	1.00
HC408	3"	4.31	3" - 8 NPT	1.22
HC409	31⁄2"	4.81	31⁄2" - 8 NPT	1.23
HC410	4"	5.31	4" - 8 NPT	1.23

Note: Product must be installed in accordance with applicable national and local electrical codes.

For use with rigid steel conduit.

Certifications / Standards:




3-Part Specification: 26 05 33.53 Tools and Calculators

— Conforms to:

- comornis to:
- UL Listed – File number: E23018
 - File number: E23018

Material / Finishes:

- Connector cast iron, zinc plated
- Locknut steel, zinc plated



Product search

electrification.us.abb.com (US/LATAM) tnb.ca.abb.com (Canada) abb.com

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction – in whole or in part – is forbidden without prior written consent of ABB. © 2023 ABB Installation Products Inc. and/or its related companies. All Rights Reserved.