




T&B Fittings







INSULATOR GLUED IN PLACE



SEALING

STAINLESS

STEEL 316 GLAND NUT

RING

NOTES:

- 1. ALL FITTINGS (BODY AND GLAND NUT) ARE MADE FROM STAINLESS STEEL TYPE 316.
- 2. FITTINGS ARE MANUFACTURED WITH NPT THREADS PER ANSI/ASME B1.20.1.
- 3. FITTINGS ARE UL LISTED LIQUIDTIGHT & CSA CERTIFIED, DUST TIGHT & WATERTIGHT.
- 4. FITTINGS ARE AVILABLE WITH ZINC PLATED STEEL AND STAINLESS STEEL TYPE 316 GROUND CONES.
- 5. FITTINGS WITH STAINLESS STEEL TYPE 316 GROUND CONES ARE NOT UL LISTED OR CSA CERTIFIED.
- 5. TO ORDER FITTING WITH SS TYPE 316 GROUND CONES, ADD (-6) TO CATALOG NUMBERS IN TABLE BELOW (EX. 5342SST6-6).
- 6. ALL INSULATED FITTINGS HAVE 105° C RATING. TO ORDER FITTINGS WITH HIGH TEMPERATURE INSULATORS AND INNER SEALING RINGS RATED FOR 150° C, ADD (HT) TO CATALOG NUMBERS IN TABLE BELOW (EX. 5342SST6HT).
- 7. TO ORDER FITTINGS WITH SS TYPE 316 GROUND CONE AND HIGH TEMPERATURE INSULATORS & INNER SEALING RING, ADD (-6HT) TO CATALOG NUMBERS IN TABLE BELOW (EX. 5342SST6-6HT).
- 8. ALL DIMENSIONS ARE FOR REFERENCE ONLY.

| CAT. No. | SIZE | DESCRIPTION | DIM "A" | DIM "B" | DIM "C" |
|----------|-------|------------------------------------|---------------|---------------|---------------|
| 5341SST6 | 3/8 | 45° LIQUID TIGHT INSULATED FITTING | 2.18 (55.37) | 1.14 (28.96) | 1.43 (36.32) |
| 5342SST6 | 1/2 | 45° LIQUID TIGHT INSULATED FITTING | 2.37 (60.20) | 1.33 (33.78) | 1.76 (44.70) |
| 5343SST6 | 3/4 | 45° LIQUID TIGHT INSULATED FITTING | 2.70 (68.58) | 1.64 (41.66) | 2.10 (53.34) |
| 5344SST6 | 1 | 45° LIQUID TIGHT INSULATED FITTING | 3.32 (84.33) | 1.87 (47.50) | 2.40 (60.96) |
| 5345SST6 | 1 1/4 | 45° LIQUID TIGHT INSULATED FITTING | 3.90 (99.06) | 2.25 (57.15) | 2.86 (72.64) |
| 5346SST6 | 1 1/2 | 45° LIQUID TIGHT INSULATED FITTING | 4.34 (110.24) | 2.56 (65.02) | 3.21 (81.53) |
| 5347SST6 | 2 | 45° LIQUID TIGHT INSULATED FITTING | 5.00 (127.00) | 3.05 (77.47) | 3.85 (97.76) |

| GENERAL NOTES | | | | Thomas@Betts | | |
|--|---|-----------|----------|---------------------------|--|--|
| 1. ALL DIMENSIONS ARE FOR REFERENCE ONLY. | www.tnb.com | | | A Member of the ABB Group | | |
| DIMENSIONS IN BRACKETS [] ARE IN METRIC UNITS. | DESCRIPTION: SALES DRAWINGS FOR 45 DEGREE | | | | | |
| REVISIONS | INSULATED STAINLESS STEEL LIQUID-TIGHT FITTINGS | | | | | |
| 1 000 000 (0047400) | INSULATED STAINLESS STEEL EIQUID-HIGHT FITTINGS | | | | | |
| SEE ERN (2017186) FOR APPROVAL SIGNATURES | ORIGINAL PROJECT NO / (ERN NO) | SHEET NO: | REV. NO: | DRAWING NO: | | |
| & RELEASE DATE. PROJECT NO: 012D000129 | 012D000129 / (2017066) | 1 OF 1 | 1 | WSD-001574 | | |