




# Ty-Rap

## NOTES

1. MATERIAL: WEATHERABLE NYLON 6,6 BLACK
2. IEC 62275 TYPE 2 CLASSIFICATION
3. OPERATING TEMPERATURE: -60°C TO 85°C  
(-76°F TO 185°F)
4. MINIMUM INSTALLATION TEMPERATURE:  
0°C (32°F)
5. ADD "5" TO DENOTE PACK  
QTY OF 100 TIES (e.g. "TY525M-9")
6. ALL TIES UL62275 TYPE 2 IS  
(EXCEPT TY23MX-0 & TY24MX-0, TYPE 2)



CATALOG NUMBER	A IN [mm]	B IN [mm]	C IN [mm]	D IN [mm]	E IN [mm]	TENSILE STRENGTH LBF [N]	MIN BUNDLE DIAMETER IN [mm]	MAX BUNDLE DIAMETER IN [mm]	MIL-SPEC NUMBER
TY25MX-0	7.31 [185]	.184 [4.67]	.043 [1.09]	.215 [5.46]	.320 [8.12]	50 [222]	.138 [3.5]	1.75 [44.5]	MS3367-1-0
TY28MX-0	14.19 [360]	.185 [4.7]	.047 [1.19]	.210 [5.33]	.310 [7.87]	50 [222]	.138 [3.5]	4.00 [101]	MS3667-2-0
TY27MX-0	13.4 [340]	.275 [7]	.065 [1.65]	.295 [7.4]	.508 [12.9]	120 [534]	.236 [3.54]	3.5 [89]	MS3667-3-0
TY23MX-0	3.62 [91.9]	.090 [2.29]	.082 [2.08]	.153 [3.89]	.186 [4.71]	18 [80]	.08 [2]	.625 [15.88]	MS3667-4-0
TY24MX-0	5.5 [139]	.140 [3.56]	.041 [1.04]	.178 [4.51]	.248 [6.29]	40 [177.9]	.08 [2]	1.125 [28.6]	MS3667-5-0
TY29MX-0	30.34 [770]	.273 [6.93]	.060 [1.52]	.320 [8.13]	.496 [12.6]	120 [534]	.236 [6]	9.00 [228]	MS3667-6-0
TY253MX-0	11.4 [289]	.185 [4.70]	.047 [1.19]	.210 [5.33]	.310 [7.87]	50 [222]	.138 [3.5]	3.00 [76]	MS3667-7-0

REVISIONS		GENERAL NOTES		DESCRIPTION:			ABB	
0	SEE ERN ( **** ) FOR APPROVAL SIGNATURES & RELEASE DATE. PROJECT NO: ****	1. ALL DIMENSIONS ARE FOR REFERENCE ONLY. 2. DIMENSIONS IN BRACKETS [ ] ARE IN METRIC UNITS.	TY-RAP MIL-SPEC CABLE TIES - BLACK					
				ORIGINAL PROJECT NO / (ERN NO)	SHEET NO:	REV. NO:	DRAWING NO:	
				PROJECT NO: FM40183/(ERN NO: 2018021)	1 OF 1	0	WSD-001838	

THIS DRAWING IS INTENDED FOR DESCRIPTIVE PURPOSES ONLY. AND THE RIGHT IS RESERVED TO DEViate FROM ANY OF THE DETAILS SHOWN HEREON.  
COPYRIGHT ABB GROUP. ALL RIGHTS RESERVED. PROPRIETARY AND CONFIDENTIAL.