

# SAFETY DATA SHEET

# 1. Identification

Product identifier	OCAL Spray Patch- Blue
Other means of identification	
SDS number	SDS-00023
Product code	SPRAY-B
Recommended use	Vinyl Resin Coating.
<b>Recommended restrictions</b>	None known.
Manufacturer/Importer/Supplier/	Distributor information
Company name	Thomas & Betts Corporation
Address	8155 T & B Boulevard
	Memphis, TN 38125
	USA
Telephone	901-252-5000 ext.8324
E-mail	Not available.
Emergency phone number	For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night +1 703-741-5970

# 2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 1A
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (central nervous system, respiratory system)
OSHA defined hazards	Not classified.	

Label elements

Signal word

Hazard statement

Extremely flammable aerosol. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May cause cancer. Suspected of damaging the unborn child. May cause damage to organs (central nervous system, respiratory system) through prolonged or repeated exposure.

#### Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Danger

Response	If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water/. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

# 3. Composition/information on ingredients

tures

Eye contact

Most important

treatment needed **General information** 

Indication of immediate

Ingestion

delayed

Chemical name		CAS number	%
4-Methylpentan-2-one		108-10-1	30-40
Toluene		108-88-3	30-40
Vinyl chloride		75-01-4	5-10
2-Methoxy-1-methylethyl acetate		108-65-6	1-5
Vinyl acetate		108-05-4	1-5
Composition comments	All concentrations are in percent by weight unless percent by volume.	ingredient is a gas. Gas	s concentrations are in
4. First-aid measures			
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.		
Skin contact	Take off immediately all contaminated clothing. Wash off with soap and water. Get medical attention if irritation develops and persists.		

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Skin irritation. May cause redness and pain. Severe eye symptoms/effects, acute and irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed. medical attention and special

> IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

# 5. Fire-fighting measures

Suitable extinguishing media	Foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.
General fire hazards	Extremely flammable aerosol.
6. Accidental release mea	asures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area).
	Large Chilley Dike the enilled meterial where this is nearly black has a near combustible meterial like

Large Spills: Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not breathe mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

### **Occupational exposure limits**

### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Туре	Value	
Vinyl chloride (CAS 75-01-4)	STEL	5 ppm	
	TWA	1 ppm	
US. OSHA Table Z-1 Limits for Air 0	Contaminants (29 CFR 1910.1	000)	
Components	Туре	Value	
4-Methylpentan-2-one (CAS 108-10-1)	PEL	410 mg/m3	
,		100 ppm	
US. OSHA Table Z-2 (29 CFR 1910.7	1000)		
Components	Туре	Value	
Toluene (CAS 108-88-3)	Ceiling	300 ppm	
	TWA	200 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
4-Methylpentan-2-one (CAS 108-10-1)	STEL	75 ppm	
,	TWA	20 ppm	

# **US. ACGIH Threshold Limit Values**

Components	Туре	Value	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Vinyl acetate (CAS 108-05-4)	STEL	15 ppm	
	TWA	10 ppm	
Vinyl chloride (CAS	TWA	1 ppm	

### 75-01-4)

### **US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Туре	Value	
4-Methylpentan-2-one (CAS 108-10-1)	STEL	300 mg/m3	
		75 ppm	
	TWA	205 mg/m3	
		50 ppm	
Toluene (CAS 108-88-3)	STEL	560 mg/m3	
		150 ppm	
	TWA	375 mg/m3	
		100 ppm	
Vinyl acetate (CAS 108-05-4)	Ceiling	15 mg/m3	
		4 ppm	

#### US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Туре	Value	
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TWA	50 ppm	

#### **Biological limit values**

#### **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
4-Methylpentan-2-one (CA 108-10-1)	S1 mg/l	Methyl isobutyl ketone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

#### **Exposure guidelines**

US - California OELs: Skin	designation	
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)		Can be absorbed through the skin.
Toluene (CAS 108-88-3)		Can be absorbed through the skin.
Vinyl chloride (CAS 75-01-4)		Can be absorbed through the skin.
US - Minnesota Haz Subs:	Skin designation applies	-
Toluene (CAS 108-88-3	)	Skin designation applies.
Appropriate engineering controls		pically 10 air changes per hour) should be itions. If applicable, use process enclosure

ing Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

#### Individual protection measures, such as personal protective equipment

 Eye/face protection
 Wear safety glasses with side shields (or goggles).

 Skin protection
 Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

 Skin protection
 Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection	Chemical respirator with organic vapor cartridge.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Blue.
Odor	Solvent.
Odor threshold	86.2
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	57.2 °F (14 °C)
Flash point	-0.4 °F (-18.0 °C)
Evaporation rate	2.1 (BUAC=1)
Flammability (solid, gas)	Extremely flammable aerosol.
Upper/lower flammability or expl	losive limits
Flammability limit - lower (%)	1
Flammability limit - upper (%)	6
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	1486.4 mm Hg
Vapor density	3
Relative density	0.921
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	< 50 SUS
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC (Weight %)	4.69 lb/gal

# 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Aluminum. Peroxides.
Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

# **11. Toxicological information**

### Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Skin irritation. May cause redness and pain. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation.

### Information on toxicological effects

Acute toxicity	Harmful if inhaled. Narcotic effects. May cause respiratory irritation.		
Components	Species	Test Results	
2-Methoxy-1-methylethyl acetate	e (CAS 108-65-6)		
Acute			
Dermal			
LD50	Rabbit	> 5000 mg/kg	
4-Methylpentan-2-one (CAS 108	-10-1)		
Acute			
Inhalation			
LC50	Rat	2000 - 4000 ppm, 4 Hours	
Toluene (CAS 108-88-3)			
Acute			
Dermal			
LD50	Rabbit	14.1 ml/kg	
Inhalation	_		
LC50	Rat	49000 mg/m³, 4 Hours	
Oral			
LD50	Rat	5580 mg/kg	
Vinyl acetate (CAS 108-05-4)			
Acute			
Oral		2222 "	
LD50	Rat	2920 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye irritation		
Respiratory or skin sensitization	on		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected	to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	May cause cancer.		
IARC Monographs. Overal	I Evaluation of Carcinogenicity	,	
4-Methylpentan-2-one (CAS 108-10-1) Toluene (CAS 108-88-3) Vinyl acetate (CAS 108-05-4) Vinyl chloride (CAS 75-01-4) <b>NTP Report on Carcinogens</b>		2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans. 2B Possibly carcinogenic to humans. 1 Carcinogenic to humans.	
Vinyl chloride (CAS 75-	01-4)	Known To Be Human Carcinogen.	
	ted Substances (29 CFR 1910.	001-1050)	
Vinyl chloride (CAS 75-	•	Cancer	
Reproductive toxicity	Suspected of damaging the u	inborn child.	

Specific target organ toxicity - single exposure	May cause respiratory irritation. May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	May cause damage to organs (central nervous system, respiratory system) through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

# 12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.			
Components		Species	Test Results	
Toluene (CAS 108-88-3)				
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	5 46 - 9 83 mg/L 48 hours	

Crustacea	EC30	water nea (Daprinia magna)	5.46 - 9.63 mg/l, 46 hours
Fish	LC50	Pink salmon (Oncorhynchus gorbuscha)	6.86 - 8.48 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

#### **Bioaccumulative potential**

Partition coefficient n-octa	nol / water (log Kow)	
4-Methylpentan-2-one (CAS 108-10-1)		1.31
Toluene (CAS 108-88-3)		2.73
Vinyl acetate (CAS 108-05-4	)	0.73
Mobility in soil	No data available.	
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.	

# 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

# 14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No
Special precautions for user	• Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols

Trenew orthogonal class (a	- )					
Transport hazard class(e Class	-					
Subsidiary risk	2					
Label(s)	- 2.1					
Packing group	Not applical	hle				
Environmental hazards	No	510.				
ERG Code	10L					
Special precautions for u		instructions S	DS and emergency pro	cedures before handlin	a	
MDG	-				9.	
UN number	UN1950					
UN proper shipping name Transport hazard class(es		5				
Class	2					
Subsidiary risk	-					
Label(s)	2.1					
Packing group	Not applical	ole.				
Environmental hazards						
Marine pollutant	No					
EmS	Not availabl	e.				
Special precautions for u ransport in bulk according to nnex II of MARPOL 73/78 an ne IBC Code	ser Read safety Not establis	instructions, S	DS and emergency pro	cedures before handlin	g.	
5. Regulatory informati	on					
S federal regulations		This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.				
TSCA Section 12(b) Expo	rt Notification (	40 CFR 707, Si	ubpt. D)			
Not regulated.						
OSHA Specifically Regula	ted Substance	s (29 CFR 1910	).1001-1050)			
Vinyl chloride (CAS 75		•	Cancer			
		Central nervous system				
			Liver			
			Blood			
			Flammability			
CERCLA Hazardous Subs	stance List (40 (	CFR 302.4)				
4-Methylpentan-2-one	(CAS 108-10-1)		LISTED			
Toluene (CAS 108-88-			LISTED			
Vinyl acetate (CAS 108	3-05-4)		LISTED			
Vinyl chloride (CAS 75	-01-4)		LISTED			
uperfund Amendments and	Reauthorization	Act of 1986 (9	SARA)			
Hazard categories		Hazard - Yes zard - Yes - Yes azard - Yes				
SARA 302 Extremely haz	•					
-	CAS number	Reportable	Threshold	Threshold	Threshold	
	SAS number	quantity (pounds)	planning quantity (pounds)	planning quantity, lower value (pounds)	planning quantity, upper value (pounds)	
Vinyl acetate	08-05-4	5000	1000			
SARA 311/312 Hazardous chemical	No					
SARA 313 (TRI reporting)			0.4.0	0/ 1 /		
Chemical name			CAS number	% by wt.		
4-Methylpentan-2-one			108-10-1	30-40		
Toluene			108-88-3	30-40		

OCAL Spray Patch- Blue

SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.
Vinyl chloride		75-01-4	5-10
Vinyl acetate		108-05-4	1-5
ther federal regulations			
	ion 112 Hazardous Air Pol	llutants (HAPs) List	
4-Methylpentan-2-one Toluene (CAS 108-88- Vinyl acetate (CAS 10 Vinyl chloride (CAS 75 Clean Air Act (CAA) Sect	-3) 8-05-4)	ase Prevention (40 CFR	68.130)
Vinyl acetate (CAS 10 Vinyl chloride (CAS 75	8-05-4)		
Safe Drinking Water Act (SDWA)	Not regulated.		
Drug Enforcement A Chemical Code Num		2, Essential Chemicals (2	21 CFR 1310.02(b) and 1310.04(f)(2) and
Toluene (CAS 108	-	6715 6594	
-		-	Mixtures (21 CFR 1310.12(c))
4-Methylpentan-2 Toluene (CAS 108	-one (CAS 108-10-1) 8-88-3)	35 %WV 35 %WV	
	al Mixtures Code Number		
	-one (CAS 108-10-1)	6715	
Toluene (CAS 108	. ,	594	
S state regulations			
US. Massachusetts RTK	- Substance List		
4-Methylpentan-2-one Toluene (CAS 108-88- Vinyl acetate (CAS 10 Vinyl chloride (CAS 75 <b>US. New Jersey Worker</b> a	-3) 8-05-4)	Now Act	
4-Methylpentan-2-one Toluene (CAS 108-88- Vinyl acetate (CAS 10 Vinyl chloride (CAS 75	(CAS 108-10-1) -3) 8-05-4)		
4-Methylpentan-2-one Toluene (CAS 108-88- Vinyl acetate (CAS 10 Vinyl chloride (CAS 75	(CAS 108-10-1) -3) 8-05-4)		
US. Rhode Island RTK 4-Methylpentan-2-one Toluene (CAS 108-88- Vinyl acetate (CAS 10 Vinyl chloride (CAS 75	-3) 8-05-4)		
US. California Propositio WARNING: This produ harm.		nown to the State of Califo	ornia to cause birth defects or other reproductive
=		Reproductive Toxicity (	(CRT): Listed substance
ternational Inventories			
<b>Country(s) or region</b> Australia	<b>Inventory name</b> Australian Inventory of	Chemical Substances (A	On inventory (yes/no) ICS) Ye
	Domestic Substances		Ye
Canada			

OCAL Spray Patch- Blue

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date	08-December-2015
Revision date	12-May-2016
Revision #	2
HMIS® ratings	Health: 2* Flammability: 4 Physical hazard: 0
NFPA ratings	2 0

Disclaimer

Thomas & Betts Corporation cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.