SAFETY DATA SHEET



1. Identification

Product identifier Sealing Cement

Other means of identification

SDS number SDS-00030

Product code EXSC-16, EXSC-160, EXSC-2, EXSC-8

Recommended use Sealing cement

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Company name Thomas & Betts Corporation

Address 8155 T & B Boulevard

Memphis, TN 38125

USA

Telephone 901-252-5000 ext.8324

E-mail Not available.

Emergency phone number For Hazardous Materials [or Dangerous Goods] Incident

Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night +1 703-741-5970

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Carcinogenicity Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated Category 2

exposure

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May

cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause damage to organs through prolonged or

repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face

protection.

Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash

before reuse.

Sealing Cement SDS US

931230 Revision: 3 Revision date: 13-May-2016 Issue date: 30-November-2015

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Portland Cement	65997-15-1	60 - 70
Quartz	14808-60-7	20 - 30
Calcium sulfate	7778-18-9	1 - 5

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials. Do not use water jet as an extinguisher, as this will spread the fire.

Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters During fire, gases hazardous to health may be formed.

Move containers from fire area if you can do so without risk.

Fire fighting equipment/instructions

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Use a vacuum cleaner. If not possible collect using a shovel, broom or the like. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid discharge into drains, water courses or onto the ground. **Environmental precautions**

Sealing Cement SDS US

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Eye/face protection Skin protection

Hand protection

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Calcium sulfate (CAS 7778-18-9)	PEL	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
Portland Cement (CAS 65997-15-1)	PEL	5 mg/m3	Respirable fraction.
US. OSHA Table Z-3 (29 CF	R 1910 1000)	15 mg/m3	Total dust.
Components	Туре	Value	Form
Portland Cement (CAS 65997-15-1)	TWA	50 mppcf	
Quartz (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
,		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Calcium sulfate (CAS 7778-18-9)	TWA	10 mg/m3	Inhalable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to	o Chemical Hazards		
Components	Туре	Value	Form
Calcium sulfate (CAS 7778-18-9)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
logical limit values	No biological exposure limits noted for the ingredient(s).		
osure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
oropriate engineering trols	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establ wash facilities and emergency shows	pplicable, use process enclosur tain airborne levels below recor ished, maintain airborne levels	es, local exhaust ventilation nmended exposure limits. I to an acceptable level. Eye

Sealing Cement SDS US

Wear safety glasses with side shields (or goggles) and a face shield.

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

931230 Revision: 3 Revision date: 13-May-2016 Issue date: 30-November-2015

supplier.

Skin protection

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Respiratory protection Use a particulate filter respirator for particulate concentrations exceeding the Occupational

Exposure Limit.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Solid. **Physical state**

Solid. Powder solid with some granular material **Form**

Color Not available.

Odor Mild.

Odor threshold Not available. pН Not available. Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

Flash point Not available. 7.70 (air = 1)**Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) Vapor pressure Not available. Not available. Vapor density

Relative density 2.557

Solubility(ies)

Insoluble Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Not explosive. **Explosive properties Oxidizing properties** Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Powerful oxidizers. Fluorine. Chlorine trifluoride. Oxygen fluoride

Sealing Cement SDS US products

Powerful oxidizers.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye damage.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause respiratory irritation.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker

protection against silicosis can be consistently assured by respecting the existing regulatory

occupational exposure limits. Suspected of causing cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

May cause damage to the following organs through prolonged or repeated exposure: Respiratory

system.

Aspiration hazard Not an aspiration hazard.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Sealing Cement SDS US

Bioaccumulative potential No data available.

Mobility in soil This substance has low mobility in the environment.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Sealing Cement SDS US 6/7

931230 Revision: 3 Revision date: 13-May-2016 Issue date: 30-November-2015

US state regulations

US. Massachusetts RTK - Substance List

Calcium sulfate (CAS 7778-18-9) Portland Cement (CAS 65997-15-1)

Quartz (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Calcium sulfate (CAS 7778-18-9) Portland Cement (CAS 65997-15-1)

Quartz (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium sulfate (CAS 7778-18-9) Portland Cement (CAS 65997-15-1) Quartz (CAS 14808-60-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Quartz (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date30-November-2015Revision date13-May-2016

Revision # 3

United States & Puerto Rico

HMIS® ratings Health: 2*

Flammability: 0 Physical hazard: 0 Personal protection: E

NFPA ratings



Disclaimer

Thomas & Betts Corporation cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Sealing Cement SDS US

931230 Revision: 3 Revision date: 13-May-2016 Issue date: 30-November-2015

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).